



TEC ROLL 800 D/S

Product Information

Double-sided transparent adhesive tape coated with a modified acrylic adhesive.

TEC ROLL 800 D/S is covered with a 90 g/m² silicone-paper (white) on both sides.

The acrylic adhesive has an excellent resistance against UV, aging and humidity.

Especially to be emphasised are the following properties:

- Mounting of digital prints, photos and posters on various surfaces
- Suitable for universal use

Storage Durability

Can be stored for 2 years in original packing at 20-25°C and 50% humidity.

Technical Data

Carrier:	PET-Film, transparent
Adhesive:	Acrylic, modified
Liner:	Silicone-paper, white (90 g/m ²)
Adhesion [N/cm]:	3,00 +/- 10 %
Thickness [mm]:	0,023 +/- 5 %
Temperatureresistance:	-20 – +80 °C

Standard Dimensions

1050 mm x 50 m
1372 mm x 50 m
1550 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

KEMICA S.r.l.

Via F.lli Rusjan, 76 - Frazione Rupa
34070 Savogna d'Isonzo (GO) - ITALIA

Phone: +39 0481 882 501
Fax: +39 0481 882 440

E-Mail: info@kemicasrl.it
Internet: www.kemica.it

03/05/2017

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.